

Message Specifications Guide



The CBORD Group, Inc.

Ithaca, NY

Version: Win2.1
January 2016
© 2016, The CBORD Group, Inc.
All Rights Reserved

Contents:

<i>HL7 (Health Level 7)</i>	3
<i>ADT Specifications</i>	4
<i>Orders Specifications</i>	14
<i>Enteral (Tube Feeding – TF) Orders Specifications</i>	20
<i>Basic (Non-HL7)</i>	23

HL7 (Health Level 7)

Intended for use with HL7 Standards, Versions 2.1 and higher (ADT) and 2.2 and higher (Orders). The following link to CBORD's web site has a copy of the latest CBORD Interface Specifications along with sample data and other great information.

ADT and Orders Interface Link (Info Sheets Tab): <http://hcl.cbord.com/products/product.asp?id=193>

HL7 Minimum Lower Layer Protocol (MLLP)

The HL7 encoded messages must be enclosed by special characters using the HL7 Minimal Lower Layer Protocol. Maximum transaction size allowed: 20K.

<SB><HL7 message><EB><CR>

Where <SB> = 0B hex, <EB> = 1C hex, <CR> = Carriage Return.

HL7 Acknowledgments

Positive (ACK) or negative (NAK) acknowledgments can be provided to the HIS upon receipt of each transaction. The ACK will signal that the transaction has been received, and can therefore trigger the next transaction to be sent. A NAK will signal that the transaction may have an error.

CBORD's HL7 Acknowledgments are formatted in accordance with HL7 Standards, Version 2.1 and higher.

<u>Segment</u>	<u>Field</u>	<u>Description</u>
MSH		Message Header
MSA	1	Acknowledgment code (AA, AE, AR)
MSA	2	Message Control ID
MSA	4	Expected Sequence Number
ERR	1^3	Application Level Error (optional)

HL7 Sequence Number Checking

Sequence number checking is optional. If a sequence number is found to be in error, the CBORD acknowledgment code in MSA:1 (MSA segment, field 1) will be AR. The expected sequence number will be in MSA:4. The response of the sending systems should be to send the transaction with the correct sequence number.

To resynchronize sequence numbers in an HL7 environment:

If the CBORD interface receives a transaction with a sequence number of -1, it will respond with a -1 as the expected sequence number in MSA:4, and will accept any sequence number greater than 0 *in the next message it receives*. (The resynchronizing sequence number comes from the sending application.)

If *that next message* received by CBORD contains a sequence number less than 1 (except for -1 which is used to start the resynchronization process), it will respond with the next expected sequence number. The "next expected sequence number" is an increment of 1 over the sequence number of that last message processed prior to the resynchronizing sequence. (The resynchronizing sequence number comes from CBORD.)

The HL7 acknowledgment code used in each of the above instances is AA. During resynchronization, data is not processed from the transaction and the interface console window is only used to display the status of the resynchronization. Upon restart of the interface, any sequence number is accepted.

HL7 Null Definition

A null (empty) field is recognized by its field separators (before and after) being contiguous with no characters in between.

HL7 ADT Interface Specifications

ADT Specifications

HL7 Event Types	Action Taken By CBORD
A01 Admit a Patient	Admit
A02 Transfer a Patient	Transfer
A03 Discharge a Patient	Discharge
A04 Register a Patient	Admit
A05 Pre-admit a Patient	Admit
A06 Transfer Outpatient to Inpatient	Admit
A07 Transfer Inpatient to Outpatient	Discharge
A08 Update Patient Information	Update
A09 Patient Departing	Discharge
A10 Patient Arriving	Admit
A11 Cancel Admit	Discharge
A12 Cancel Transfer	Transfer
A13 Cancel Discharge	Cancel Discharge
A17 Swap Patients' Locations	2 Transfers. Requires 2 PID and 2 PV1 segments (one pair per patient)
A21 Leave of Absence – Exit	Discharge
A22 Leave of Absence – Return	Cancel Discharge
A31 Update Patient Information	Update
A32 Cancel Patient Arriving	Discharge
A33 Cancel Patient Departing	Cancel Discharge
A18 Merge Patient Information A34 Update Patient ID A35 Update Patient Account Number A36 Update Patient ID and Account Number	Update Patient Identifiers for current visit, unless Identifier is already in use.
A52 Cancel Leave of Absence	Cancel Discharge
A53 Cancel Patient Return from Leave of Absence	Discharge

HL7 ADT Message Layouts

The order of the segments, per record types, is defined below. Following these descriptions of the message structures, you will find more detailed definitions of the segments that are supported.

A01 Admit a Patient; A04 Register a Patient, A05 Pre-admit a Patient, A08 Update Patient Information, A13 Cancel Discharge, A31 Update Patient Information

<u>Supported Segments</u>	<u>Required</u>	<u>Description</u>
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification
<i>PD1</i>		<i>Patient Demographic Information (not used)</i>
<i>NK1</i>		<i>Next of Kin (not used)</i>
PV1	Y	Patient Visit
PV2		Patient Visit – additional information
<i>DB1</i>		<i>Disability (not used)</i>
OBX		Observations/Patient Profile
AL1		Allergies
NTE		Allergy Notes
DG1		Diagnosis Information
<i>DRG</i>		<i>Diagnosis Related Group (not used)</i>
<i>PR1</i>		<i>Procedures (not used)</i>
<i>ROL</i>		<i>Role (not used)</i>
<i>GT1</i>		<i>Guarantor (not used)</i>
<i>IN1</i>		<i>Insurance (not used)</i>
<i>IN2</i>		<i>Insurance Additional Info. (not used)</i>
<i>IN3</i>		<i>Insurance Additional Info - Cert. (not used)</i>
<i>ACC</i>		<i>Accident Information (not used)</i>
<i>UB1</i>		<i>Universal Bill Information (not used)</i>
<i>UB2</i>		<i>Universal Bill 92 Information (not used)</i>

A06 Transfer Outpatient to Inpatient, A07 Transfer Inpatient to Outpatient

Supported Segments	Required	Description
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification
<i>PD1</i>		<i>Patient Demographic Information (not used)</i>
<i>MRG</i>		<i>Merge (not used)</i>
<i>NK1</i>		<i>Next of Kin (not used)</i>
PV1	Y	Patient Visit
PV2		Patient Visit – additional information
<i>DB1</i>		<i>Disability (not used)</i>
OBX		Observations/Patient Profile
AL1		Allergies
NTE		Allergy Notes
DG1		Diagnosis Information
<i>DRG</i>		<i>Diagnosis Related Group (not used)</i>
<i>PR1</i>		<i>Procedures (not used)</i>
<i>ROL</i>		<i>Role (not used)</i>
<i>GT1</i>		<i>Guarantor (not used)</i>
<i>IN1</i>		<i>Insurance (not used)</i>
<i>IN2</i>		<i>Insurance Additional Info. (not used)</i>
<i>IN3</i>		<i>Insurance Additional Info - Cert. (not used)</i>
<i>ACC</i>		<i>Accident Information (not used)</i>
<i>UB1</i>		<i>Universal Bill Information (not used)</i>
<i>UB2</i>		<i>Universal Bill 92 Information (not used)</i>

A02 Transfer a Patient, A21 Leave of Absence – Exit, A22 Leave of Absence – Return, A32 Cancel Patient Arriving, A33 Cancel Patient Departing, A52-Cancel Leave of Absence, A53-Cancel Patient Return from Leave of Absence

Supported Segments	Required	Description
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification
<i>PD1</i>		<i>Patient Demographic Information (not used)</i>
PV1	Y	Patient Visit
PV2		Patient Visit – additional information
<i>DB1</i>		<i>Disability (not used)</i>
OBX		Observations/Patient Profile

A03 Discharge a Patient

Supported Segments	Required	Description
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification
<i>PD1</i>		<i>Patient Demographic Information (not used)</i>
PV1	Y	Patient Visit
PV2		Patient Visit – additional information
<i>DB1</i>		<i>Disability (not used)</i>
DG1		Diagnosis Information
<i>DRG</i>		<i>Diagnosis Related Group (not used)</i>
<i>PR1</i>		<i>Procedures (not used)</i>
<i>ROL</i>		<i>Role (not used)</i>
OBX		Observations/Patient Profile

A09 Patient Departing, A10 Patient Arriving, A11 Cancel Admit, A12 Cancel Transfer

Supported Segments	Required	Description
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification
<i>PDI</i>		<i>Patient Demographic Information (not used)</i>
PV1	Y	Patient Visit
PV2		Patient Visit – additional information
<i>DB1</i>		<i>Disability (not used)</i>
OBX		Observations/Patient Profile
DG1		Diagnosis Information

A17 Swap Patient Locations

Supported Segments	Required	Description
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification for Patient 1
<i>PDI</i>		<i>Patient Demographic Information (not used)</i>
PV1	Y	Patient Visit for Patient 1
PV2		Patient Visit for Patient 1 - additional info
<i>DB1</i>		<i>Disability (not used)</i>
OBX		Observations/Patient Profile for Patient 1
PID	Y	Patient Identification for Patient 2
<i>PDI</i>		<i>Patient Demographic Information (not used)</i>
PV1	Y	Patient Visit for Patient 2
PV2		Patient Visit for Patient 2 - additional info
<i>DB1</i>		<i>Disability (not used)</i>
OBX		Observations/Patient Profile for Patient 2

A18, A34, A35, A36 Update Patient Information (Update Patient Identifiers)

Supported Segments	Required	Description
MSH	Y	Message Header
<i>EVN</i>	<i>C</i>	<i>Event (not used)</i>
PID	Y	Patient Identification
<i>PDI</i>		<i>Patient Demographic Information (not used)</i>
MRG	Y	Merge
PV1	C	Patient Visit

ADT Segments Definitions

These segment definitions include required and commonly used fields among CBORD users. For more detail on segment definitions, please refer to HL7 Standards, Versions 2.1 and higher. Most fields are variable-length fields, although field lengths in online display and reports from the Nutrition Services Suite may be limited.

MSH - Message Header Segment

MSH Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "MSH"	Message Control
1	Field Separator	R		Message Control
2	Encoding Characters	R		Message Control
3	Sending Application	C	Constant Required if Acknowledgments are used.	Filter; Acknowledgments
4	Sending Facility	C	Constant Required for some methods of multiple database updates.	Filter
5	Receiving Application	O	Constant "CBORD"	Filter
6	Receiving Facility	C	Constant Required for some methods of multiple database updates.	Filter
7	Date/Time of Message	R	CCYYMMDDHHMM	Message Control
9	Message Type Event Type	R C	Component 1=ADT Component 2=HL7 Event type code If Event type is not provided, the use of the EVN segment must be defined at implementation.	Record Type
10	Message Control ID	R	Will be returned in ACK.	Message Control
12	Version ID	O		Message Control
13	Sequence Number	C	Required for sequence number checking.	Message Control
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

EVN - Event Segment

EVN Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "EVN"	Message Control
1	Event Type	C	Required if Event Type is not valued in component 2 of MSH field 9.	Record Type
2	Event Date/Time	O	CCYYMMDDHHMM	
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

PID - Patient Identification Segment

PID Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "PID"	Message Control
3	Patient ID (Internal ID)	R	MRN. CBORD will use 24 characters.	Patient ID
4	Alternate Patient ID	O		
5	Patient Name	R	Last^First. CBORD will use 250 characters, display 24, for each Last Name and First Name. Optional: Component 3 - Middle Name or Initial Component 4 - Suffix (SR, JR, MD or PH) Component 5 - Nickname	Patient Name
7	Date of Birth	O	CCYYMMDD	Birth Date
8	Sex	O	Valid values: M, F, P or L P = Female and will check Pregnant box L = Female and will check Lactating box	Sex
10	Race Code	O	Valid values: 1002-5 American Indian or Alaska Native 2028-9 Asian 2054-5 Black or African American 2076-8 Native Hawaiian or Other Pacific Islander 2106-3 White 2131-1 Other Race If value is not provided, the field in CBORD will be set to null/empty.	Race
15	Language Code	O	Valid values for: English = en or eng Spanish = es or spa French = fr or fra	Patient's Language
17	Religion	O	ID^Description CBORD will use a total of 40 characters obtained from the Description.	Religion
18	Patient Account No.	O	CBORD will use 24 characters.	Billing ID
19	Patient SSN	O	Social Security ID. Numeric only.	Patient SSN
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

MRG - Merge Patient Information Segment

MRG Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "MRG"	Message Control
1	Prior Patient ID List	C	Component 1 is required to contain the Prior Patient MRN in order to change the patient's MRN. Component 5 may contain consistent Prior Patient identifier data. Component 6 may contain assigning facility.	Prior Patient Identifier Filter
3	Prior Patient Account Number	C	Required to change patient Billing ID. CBORD will use 24 characters.	Prior Billing ID
4	Prior Patient ID	O	Alternative location to change patient MRN.	Prior MRN
7	Prior Patient Name	O	Last^First. CBORD will use 250 characters, display 24, for each Last Name and First Name. Optional: Component 3 - Middle Name or Initial Component 4 - Suffix (SR, JR, MD or PH) Component 5 - Nickname	Patient Name
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

PV1 - Patient Visit Segment

PV1 Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "PV1"	Message Control
2	Patient Class	R	"I" designates inpatient transactions, which are most relevant to the CBORD system.	Filter
3	Patient Location	R	NURSING STATION^ROOM^BED CBORD will display 20 characters total. Values are not auto-truncated. Max lengths: NS ID=8, NS Name=15, Room/Bed=20	Room/Bed
7	Attending Doctor	O	Doctor ID^Last^First CBORD will use a total of 36 characters obtained from the Doctor's Last and First Name.	Physician
15	Ambulatory Status	O	"B6" designates sex of Female and will check Pregnant box.	Pregnant
16	VIP Indicator	O	Valid values: Y -or- N	VIP
38	Insulin Indicator	O	Valid values: Y -or- N	Insulin
44	Admit Date/Time	C	CCYYMMDDHHMM Required for Admission: If value is not provided, CBORD will use EVN or system date/time.	Admit Date/Time
45	Discharge Date/Time	C	CCYYMMDDHHMM Required for Discharge: If value is not provided, CBORD will use EVN or system date/time.	Discharge Date/Time. Filter.
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

PV2 - Patient Visit Segment – Additional Information

PV2 Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "PV2"	Message Control
12	Protocol ID	O	Protocol code	Protocol ID
40	Level of Care		"F" designates Isolation, any other value except null removes Isolation	Isolation
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

OBX - Observation Segment

OBX Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "OBX"	Message Control
1	Set ID	O		Mapping Definition
3	Observation Identifier	O	"Lactating" will check Lactating box.	Lactating
5	Observation Identifier Observation Result Value	R R	<p>Component 1: For Height: HT For Weight: WT</p> <p>Component 3: Value Valid value ranges are: <u>English Units:</u> Weight: Greater than 0 and not more than 2204 lbs. Height: Greater than 0 and not more than 1549 in.</p> <p><u>Metric Units:</u> Weight: Greater than 0 and less than 1000 kg. Height: Greater than 0 and less than 3935 cm.</p> <p>When updating height and weight, both values must be sent inside the same transaction by using multiple OBX segments.</p>	Data Type Data Value
6	Unit of Measure	O	<p>Component 1 or 2. If no U of M is provided, a constant unit of measure must be defined at implementation.</p> <p>Valid values: IN, CM, LB or KG</p>	Data Value Measure
14	Observation Date/Time	O	<p>CCYYMMDDHHMM If no value is provided, CBORD will use EVN or system date/time.</p>	Date/Time of Recorded Profile Data
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

AL1 - Allergies Segment

AL1 Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "AL1"	Message Control
2	Allergy Type	C	Required for Food Allergies: FA	Filter
3	Allergy Code	R	Multiple repetitions within this field and/or multiple AL1 segments represent concurrent allergies. Maximum Allergy codes may be limited by your reporting requirements, but all allergies are checked for meal compliance. Maximum Allergy code length is 12 characters. The codes are not case sensitive.	Allergy
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

NTE - Note Segment

NTE Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "NTE"	Message Control
3	Note Text	O	Maximum Note length may be limited by your reporting requirements. Maximum Note length is unlimited.	Allergy Notes
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

DG1 - Diagnosis Segment

DG1 Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "DG1"	Message Control
3	Diagnosis Code	O	ICD9 code. Max Length: 45	Diagnosis
4	Diagnosis Description	O	Natural language description of diagnosis.	Diagnosis
5	Diagnosis Start Date/Time	O	CCYYMMDDHHMM For use with coded diagnosis. If value is not provided, CBORD will use MSH Field 7. If value is not found in MSH Field 7, CBORD will use the system date/time.	Diagnosis Start Date/Time
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

HL7 Orders Interface Specifications

Orders Specifications

In CBORD's Nutrition Service Suite (NSS), a diet order can be composed of several diet restrictions. (One order may be 40 gram Protein, 1 gram Sodium, 1 gram Potassium, MAO, Full Liquid, and No Concentrated Sweets.) **All concurrent parts (diet restrictions) of a diet order must be entered at once, from one ORM transaction.** Entry of diet restrictions at a later time implies a new diet order that will supersede the last one as of the new one's start date and time.

All diet restrictions must be represented as coded elements; variable free text may be used in messaging but is not supported in NSS diet restrictions.

Multiple Order Control Segments (ORC) per message are supported. Orders are created based on the information from the ORC segment that they follow.

HL7 Orders Interface

HL7 Event Types	Action Taken By CBORD
NW New Order	Add new order to the card file.
CA Cancel Order	Cancel a previously sent order identified by the placer order number. Does not revoke any NTE segments attached to the order.
DC Discontinue Order	Cancel a previously sent order identified by the placer order number. Does not revoke any NTE segments attached to the order.
RP Replace Order	Cancel a previously sent order identified by the placer order number. Does not revoke any NTE segments attached to the order. Adds new order to the card file.

HL7 Orders Message Layout

The order of the segments are defined below. Following these descriptions of the message structures, you will find more detailed definitions of the segments that are supported.

NW- New Order, CA- Cancel Order, DC- Discontinue Order, RP – Replace Order

* Please see the CBORD HL7 ADT Interface specifications for segment details.

Supported Segments	Required	Description
MSH	Y	Message Header
*EVN	C	Event (not used)
NTE		Notes (not used)
*PID	Y	Patient Identification
NTE		Notes (not used)
*PV1	Y	Patient Visit
*PV2		Patient Visit – additional info
IN1		Insurance (not used)
IN2		Insurance Additional Info. (not used)
IN3		Insurance Additional Info - Cert. (not used)
GT1		Guarantor (not used)
*AL1		Allergies
*NTE		Allergy Notes
ORC	Y	Order Control
ODS	C	Order Dietary Service (required for NW)
NTE		Notes
*DG1		Diagnosis Information
*OBX		Observations/Patient Profile
NTE		Notes (not used)
ODT		Order Dietary Tray
NTE		Notes (not used)
RXO		Order Enteral (Tube Feeding - TF)
NTE		Notes (not used)
RXR		Pharmacy/Treatment Route (not used)
RXC		Pharm/Treat Component Order (not used)
NTE		Notes (not used)

Order Segments Definitions

These segment definitions include required and commonly used fields among CBORD users. For more detail on segment definitions, please refer to HL7 Standards, Versions 2.2 and higher. Most fields are variable-length fields, although field lengths in online display and reports from the Nutrition Services Suite may be limited.

MSH - Message Header Segment

MSH Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "MSH"	Message Control
1	Field Separator	R		Message Control
2	Encoding Characters	R		Message Control
3	Sending Application	C	Constant. Required if Acknowledgments are used.	Filter; Acknowledgments
4	Sending Facility	C	Constant Required for some methods of multiple database updates.	Filter
5	Receiving Application	O	Constant "CBORD"	Filter
6	Receiving Facility	C	Constant Required for some methods of multiple database updates.	Filter
7	Date/Time of Message	R	CCYYMMDDHHMM	Message Control
9	Message Type Event Type	R R	Component 1=ORM Component 2=O01	Record Type
10	Message Control ID	R	Will be returned in ACK.	Message Control
12	Version ID	O		Message Control
13	Sequence Number	C	Required for sequence number checking.	Message Control
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

ORC - Order Control Segment.

ORC Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "ORC"	Message Control
1	Order Control	R	NW, CA, DC, RP	Record Type
2	Placer Order Number	R	Alphanumeric. Maximum length is 22.	Placer Order Number
7	Quantity/Timing	R	Supported Components of ORC:7 are: 1 <quantity> For use with Supplements. If value is not provided, CBORD will use a default quantity of one for each supplement. If value is provided, it will be used for each supplement that is specified within that ORC grouping. 2 <interval> 3 <duration> 4 <start date/time> CCYYMMDDHHMM 5 <end date/time> CCYYMMDDHHMM 8 <text> 9 <order sequencing>	Quantity and Timing data
10	Entered By	O	Maximum length is 7. Value is auto-truncated.	Authorization
11	Verified By	O	If no value is provided in ORC Field 10, CBORD will use this field.	Authorization
12	Ordering Provider	O	If no value is provided in ORC Field 11, CBORD will use this field.	Authorization
15	Order Effective	C	CCYYMMDDHHMM If no value is provided in ORC Field 7 component 4, CBORD will use this field. If no value is then provided in this field, CBORD will use the system date/time.	Start Date
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

ODS - Order Dietary Service Segment

ODS Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "ODS"	Message Control
1	Dietary Service Type	R	D = Diet S = Supplement	Message Control
2	Service Period	C	<p>For use with Supplements. If value is not provided, CBORD will apply supplements to All Meals.</p> <p><u>Meal Periods:</u> 1 = Breakfast 2 = 10 AM Snack 3 = Lunch 4 = 2 PM Snack 5 = Dinner 6 = HR Snack 7 = Catering, AM 8 = Brunch 9 = Catering, Afternoon 10 = Catering, Late 11 = All Day</p> <p>*User defined Meal Periods can be created in NSS to represent multiple meal period groups (i.e. BLD = Breakfast/Lunch/Dinner). Value must contain at least one alpha character for interfacing.</p> <p>A single Meal Period or User defined Meal Period, will be applied to the Supplements defined in the same ODS segment.</p> <p>Within an ORC grouping, ODS segments with the same Meal Periods will be combined as one order.</p> <p>Multiple repetitions within this field represent concurrent Meal Periods. Translation is then used to translate multiple Meal Periods into a single User defined Meal Period.</p>	Meal period
3	Dietary Service	R	<p>Multiple repetitions within this field represent concurrent Diet Restrictions or Supplements, as designated by the first field of the ODS segment. Multiple ODS segments are supported.</p> <p>Maximum Diet Restriction codes may be limited by your reporting requirements, but all Diet Restrictions are checked for meal compliance.</p> <p>Maximum Diet Restriction code length is 12 characters. Maximum Supplement code length is 25 characters. Diet Restriction and Supplement codes are not case sensitive.</p>	Diet Restrictions or Supplements
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

NTE - Note Segment

NTE Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "NTE"	Message Control
3	Note Text	O	Maximum Note length may be limited by your reporting requirements. Maximum Note length is unlimited. Note will be associated with the ODS that it follows, either a Diet Order or Supplement Order as defined above.	Diet Order or Supplement Notes
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

ODT - Order Dietary Tray Segment

ODT Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "ODT"	Message Control
1	Tray Type	O	Service "location" coded for the service type: MSG = Tray Ticket Message PMN = Personal Menu Note Early = Early Tray Late = Late Tray RS = Room Service NoRS = No Room Service	Service Type
2	Service Period	O	Repetition 1: Start Meal Repetition 2: End Meal For use with Services. If value is not provided, CBORD will apply service to All Meals. <u>Meal Periods:</u> 1 = Breakfast 2 = 10 AM Snack 3 = Lunch 4 = 2 PM Snack 5 = Dinner 6 = HR Snack 7 = Catering, AM 8 = Brunch 9 = Catering, Afternoon 10 = Catering, Late 11 = All Day	Service Meal Period
3	Text Instruction	C	Free Text message for the Tray Ticket Note or Personal Menu Note if indicated by Tray Type ODT.1	Tray Text
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

HL7 Enteral (Tube Feeding – TF) Orders Interface Specifications

Enteral (Tube Feeding – TF) Orders Specifications

The Enteral Interface will accept an Order ID, Start Date/Time, End Date/Time, and authorization to create an enteral order header. It can also cancel orders. All other data in a tube feeding order (including products, rate, strength, recipe notes and administration instructions) is put in the Order Summary Note on the enteral orders screen within the Nutrition Service Suite (NSS). To leverage the functionality of the Enteral Nutrition Support module, the user runs an NSS report (Enteral Formula List) that lists the "incomplete" enteral orders. Data entry is needed to transcribe the text note to the appropriate fields on the rest of the Enteral Order screen in each patient card file record.

HL7 Event Types	Action Taken By CBORD
NW New Order	Add new order to the card file.
CA Cancel Order	Cancel a previously sent order identified by the placer order number. Does not revoke any NTE segments attached to the order.
DC Discontinue Order	Cancel a previously sent order identified by the placer order number. Does not revoke any NTE segments attached to the order.
RP Replace Order	Cancel a previously sent order identified by the placer order number. Does not revoke any NTE segments attached to the order. Adds new order to the card file.

HL7 Enteral (Tube Feeding – TF) Orders Message Layout

The order of the segments are defined below. Following these descriptions of the message structures, you will find more detailed definitions of the segments that are supported.

NW- New Order, CA- Cancel Order, DC- Discontinue Order, RP – Replace Order

*Please see the CBORD HL7 ADT and Orders Interface specifications for segment details.

<u>Supported Segments</u>	<u>Required</u>	<u>Description</u>
MSH	Y	Message Header
*EVN	C	Event (not used)
NTE		Notes (not used)
*PID	Y	Patient Identification
NTE		Notes (not used)
*PV1	Y	Patient Visit
*PV2		Patient Visit – additional info
IN1		Insurance (not used)
IN2		Insurance Additional Info. (not used)
IN3		Insurance Additional Info - Cert. (not used)
GT1		Guarantor (not used)
*AL1		Allergies
*NTE		Allergy Notes
ORC	Y	Order Control
ODS	C	Order Dietary Service
NTE		Notes
*DG1		Diagnosis Information
*OBX		Observations/Patient Profile
NTE		Notes (not used)
ODT		Order Dietary Tray
NTE		Notes (not used)
RXO	Y	Order Enteral (Tube Feeding - TF)
NTE		Notes (not used)
RXR		Pharmacy/Treatment Route (not used)
RXC		Pharm/Treat Component Order (not used)
NTE		Notes (not used)

Order Segments Definitions

These segment definitions include required and commonly used fields among CBORD users. For more detail on segment definitions, please refer to HL7 Standards, Versions 2.2 and higher. Most fields are variable-length fields, although field lengths in online display and reports from the Nutrition Services Suite may be limited.

MSH - Message Header Segment

MSH Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "MSH"	Message Control
1	Field Separator	R		Message Control
2	Encoding Characters	R		Message Control
3	Sending Application	C	Constant. Required if Acknowledgments are used.	Filter; Acknowledgments
4	Sending Facility	C	Constant Required for some methods of multiple database updates.	Filter
5	Receiving Application	O	Constant "CBORD"	Filter
6	Receiving Facility	C	Constant Required for some methods of multiple database updates.	Filter
7	Date/Time of Message	R	CCYYMMDDHHMM	Message Control
9	Message Type Event Type	R R	Component 1=ORM Component 2=001 or 009 or Component 1=OMP Component 2=009	Record Type
10	Message Control ID	R	Will be returned in ACK.	Message Control
12	Version ID	O		Message Control
13	Sequence Number	C	Required for sequence number checking.	Message Control
	Segment Separator	R		Message Control

*R/O/C = Required / Optional / Conditional

RXO - Order Enteral (Tube Feeding - TF) Segment

RXO Field	Field Name	R/O/C*	Comments	Used by CBORD as--
0	Segment Identifier	R	Constant "RXO"	Message Control
6	Provider's Pharmacy/Treatment Instructions	R	Component 2: Order Enteral (Tube Feeding - TF) Text Notes	Enteral Order Text

*R/O/C = Required / Optional / Conditional

Basic (Non-HL7)

At this time, the CBORD Clinical Interface does not support Basic (Non-HL7) data formats.